

HOL 312



The HOL 312 is a compact solution with a redundant uplink for productions where space is limited. Extremely suitable for 'add-on' productions like events, live sports, talk shows on location, etc..



GENERAL

TRANSMISSION

Gigasat DA-150 antenna (13,75 – 14,50 GHz)
2x 400 Watt HPA (1:1 – max 70dBW EIRP)
Redundant encoding / IRD / modulation: NTT, Adtec, Ericsson, Ateame, Newtec, Enensys (HD/UHD H.264/HEVC DVBS2, DVBS2X)
Sat. Registrations with Eutelsat, SES, Intelsat
Optional 2+1 / 3+1 output, up to 8 ch multiplex

MAIN TRUCK

Length	6,00m
Height	3,50 m
Weight	3,5 tons
Width	2,0m
Generator	Onboard 8 KVA, Including UPS
Licence plate	5-VX K-09

HOL 312



PROCESSING POWER

UP TO 2 CAMS ENG

VIDEO

Blackmagic video mixer 8 inputs HD SDI with compact switching panel
Nevion video & audio matrix (32x32)
EVS frame sync & de-embedding
HDCAM player/ recorder/ SSD Hyperdeck
150 mtrs optic fiber system (IFB kit included)
Optional AVID, Adobe Premiere edit

AUDIO

Yamaha 16 ch audio mixer with LUFS R128 monitoring
Dolby-E/Dolby Atmos pass-through
RTS Zeus comms matrix
Motorola UHF & handheld radios
2x GSM phone hybride for IFB & production
4G Wifi router, optional IPcodec, sat comms



CONTACT

sales.nl@emglive.com
www.emglive.com